BLIXER® 15



| Number of 200 g portions : | 15 to 50 portions |
|----------------------------------|-------------------|
| Quantity processed per operation | 3 to 10 kg |

A SALES FEATURES

Blixer 15 is designed to prepare texture-modified meals with either raw and cooked ingredients in a minimum of time.

B TECHNICAL FEATURES

Blixer 15. Three-Phase. Power 3000 W. 2 speeds. Pulse function. 15 L stainless-steel bowl with 2 handles. Bowlbase blade assembly with 3 detachable fine serrated blades included. Scraper arm and lid wiper included. 15 to 50 portions and more.

Select all the options at the back page, F part.

| C TECHNICAL DATA | | | |
|-----------------------|--------------------------------|-----------|--|
| Output power | 3000 Watts | | |
| Electrical datas | Three phase No plug includ | ded | |
| Speeds | 50Hz : 1500 c 60Hz : 1800 c | | |
| Dimensions (LxWxH |) 315 x 545 x 7 | 700 mm | |
| Rate of recyclability | 95% | | |
| Net weight | 49 kg | | |
| Supply | Amperage | Reference | |
| 400V/50/3 | 6.5 & 12 Amp | 51511 | |
| 220V/60/3 | 6.5 & 11 Amp | 51513 | |
| 380V/60/3 | 7 & 12 Amp | 51514 | |
| 230V/50/3 | 7 & 13 Amp | 51515 | |

STANDARDS

EN 12100-1 & 2 - 2004, EN 60204-1 - 2006, EN 12852, EN 60529-2000



PRODUCT FEATURES

MOTOR BASE

- Direct drive induction motor (no belt) for intensive use.
- Power 3000 Watts.
- Stainless steel motor shaft.
- Flat, easy-clean motor base.
- IP65 control panel with flush buttons.
- Magnetic safety and motor brake.
- 2 speeds: 1500 and 3000 rpm (50Hz) or 1800 and 3600 rpm (60Hz).
- Pulse function for a better cut precision.

BLIXER® FUNCTION

- 15 litre stainless-steel bowl with 2 handles for a better arip.
- Central bowl locking system for easy assembly.
- Bowl-base blade assembly with 3 fine serrated blades to ensure a perfectly uniform consistency, even when processing small quantity.
- Transparent lid to enable user to monitor processing.
- Opening in centre of lid for adding liquid or dry ingredients during processing.
- Transparent lid with bowl scraper to improve the end-product consistency and with a lid wiper to enable user to monitor processing.
- Opening in centre of lid for adding liquid or dry ingredients during processing.

INCLUDED ACCESSORIES

- Stainless steel fine serrated blade assembly (3 blades)
- Scraper arm and lid wiper



BLIXER® 15

F

OPTIONS

- Additional Fine serrated blade assembly (3 blades) -Ref. 57102
- Fine serrated blade (per unit) Ref. 59359



