




# BLUSODA BOX hot

30  
l/h45  
l/hstainless  
STEELDRY  
COOLINGGAS  
R290



fizz

hot


	BLUSODA BOX HOT 30 FIZZ	BLUSODA BOX HOT 45 FIZZ
Cooling capacity (l/h)	30	45
Max continuous supply (l)	6	12
Cold water temperature*	5 - 12 °C	
Pump	Professional membrane carbonation pump	
Cooling technology	Aluminum fusion block - stainless steel coil	
Condensation	Forced ventilation	
Refrigerant gas	R290	
Max hot water temperature	95 °C	
Boiler capacity (l)	1	
Heating capacity (l/h)	8	
Watt boiler	1000 W	
Adjustable thermostat	Yes	
Supply	230 V - 50 Hz	
Compressor power	1/8 HP	1/5 HP
Absorbed power	1200 W - 5,3 A	1285 W - 5,6 A
Working room temperature	Min 5°C - Max 35°C	
Inlet water pipe	Ø5/16" (8 mm)	
Inlet CO <sub>2</sub> pipe	Ø5/16" (8 mm)	
Typology	Undercounter	
Net weight (kg)	26	32
Gross weight (kg)	28	35
Dimensions W x D x H (mm)	260 x 416 x 416	318 x 440 x 468
Packaging dimensions (mm)	330 x 440 x 540	350 x 450 x 490



Blusoda Box Hot 30



Blusoda Box Hot 45



Dispensing options	Cold still water, cold sparkling water and hot water	
Materials	Parts in robust stainless steel and aluminum	

## OPTIONAL

Water pressure reducer	
CO <sub>2</sub> pressure reducer	
Filters	Activated carbon filter (inside)
Taps	Electronic or mechanical

\* rated at a room temp. of 25 °C and inlet water temp. of 20 °C  
For a proper installation of the system, the use of the WATER BLOCK is compulsory.

## CERTIFICATIONS

